

The importance of secondary processes on alluvial fan morphology, hazards and reworking



Lauren Vincent
The University of British Columbia

Anya Leenman,
The University of British Columbia

Supervisors:
Brett Eaton,
The University of British Columbia

Matthias Jakob,
BGC Engineering Inc.



Post-event downcutting at Turbid Creek, BC Sept 24, 2019. Photo by author.

The processes occurring between processes delivering material to the fan (primary processes) may be referred to as secondary processes.

Primary processes




Three Sisters Creek during 20 June 2013.
Photos: M. Jakob. (Church and Jakob, 2020)

Secondary processes




Post-event downcutting at Turbid Creek, BC Sept 24, 2019. Photo by author.

Secondary processes re-mobilize and rework sediment previously deposited on the fan.



(Hooke, 1967)

- Channel incision/entrenchment
- Terracing
- Channel bed armouring
- Sediment redistribution
- Down-fan migration of the intersection point



Three Sisters Creek, AB






Source: <https://d-maps.com>




Source: Google Earth (2018)

Three Sisters Creek, AB






Source: Google Earth (2018)

A stream table was used to replicate alluvial fans generated under debris flood conditions.



Photographic data were collected at 1 minute intervals and used to generate DEMs, orthomosaics and binary channel maps.



Phase 1: Fan Formation

Experiment #	Primary Process			Secondary Process			Total Est. Experiment Duration (hours)
	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	
1	100	10	5	50	0	5	4
2	100	10	5	50	0	10	6
3	100	10	5	50	0	20	10
4	100	10	5	50	0	40	18

Notes:

- Each line represents a distinct experiment and alluvial fan.
- Experiments were run until a total of 72 kg of sediment had been input into the fan.
- The total length of the experiments varied based on the duration of secondary processes.

Phase 1: Fan Formation

Experiment #	Primary Process			Secondary Process			Total Est. Experiment Duration (hours)
	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	
1	100	10	5	50	0	5	4
2	100	10	5	50	0	10	6
3	100	10	5	50	0	20	10
4	100	10	5	50	0	40	18

Notes:

- Each line represents a distinct experiment and alluvial fan.
- Experiments were run until a total of 72 kg of sediment had been input into the fan.
- The total length of the experiments varied based on the duration of secondary processes.

Phase 1: Fan Formation


Experiment #	Primary Process			Secondary Process			Total Est. Experiment Duration (hours)
	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	
1	100	10	5	50	0	5	4
2	100	10	5	50	0	10	6
3	100	10	5	50	0	20	10
4	100	10	5	50	0	40	18

Notes:


- Each line represents a distinct experiment and alluvial fan.
- Experiments were run until a total of 72 kg of sediment had been input into the fan.
- The total length of the experiments varied based on the duration of secondary processes.


Phase 2: Fan Flooding


Flood Name	Discharge (mL/s)	Sediment Feed (g/s)	Duration (mins)	No. of Repeats
A	100	10	5	3
B	150	15	5	3
C	150	20	5	3





Sediment feed (g/s)










Fan gradient was lowest adjacent to the fan axis, and highest near the fan flanks.



Secondary processes tended to produce a single centralized channel, while primary processes resulted in bifurcated flow.



Experiments with longer secondary processes had fewer avulsions and the first avulsion occurred later in the flood period.



Exp. #	Total Avulsion Count	Avg. Avulsion Timing (mins)
1	20	2.6
2	18	2.7
3	15	3.1
4	12	3.4

T_A indicates that the decrease in avulsion frequency from Experiment 1 to 4 cannot be explained entirely by increasing fan radius.

$$T_A(t) = \frac{hwr(t)}{Q_s}$$

Channel dimensions

Predicted avulsion frequency



Sediment feed rate

Exp. #	Total Avulsion Count	Predicted Avulsion Count (T_A)	Percent Change
1	20	18	+ 10%
2	18	18	0%
3	15	16	- 7%
4	12	16	- 33%


Increasing duration of secondary processes




Primary fan channel cross-section



Fan top-down view




Experiment 1 (3 h 30 min)




Experiment 4 (16 h 25 min)


Climate Change Impacts:




Increased frequency and magnitude of rainfall events




Sediment unlimited catchment




More debris laden flows
Shorter secondary process periods




Sediment limited catchment




More clearwater flows
Additional secondary processes




Climate Change Impacts:




Increased frequency and magnitude of rainfall events




Sediment unlimited catchment




More debris laden flows
Shorter secondary process periods



Sediment limited catchment



More clearwater flows
Additional secondary processes



These results highlight the importance of secondary processes in determining pre-flood conditions.



My experiments used constant flow during flooding; if you want to dig into how variable flood discharge impacts alluvial fans, check out:

[Floods on alluvial fans: implications for fan hazards, morphology and reworking](#)
by Anya Leenman EP038-0005